

Card  
Printer

**3**  
**YEARS**  
WARRANTY



**DC-7600**  
Fast and reliable



**HIGHLIGHTS AT A GLANCE:**

- High resolution printing with 600 dpi
- High productivity due to high speed printing
- Over-the-Edge full card printing
- High capacity card feeder
- Variety of smart card encoders

**DASCOM**<sup>®</sup>  
SOLUTIONS FOR BUSINESS PRINTING


# DC-7600

Retransfer print technology is the next level of Direct-to-Card technology. First, the image is printed on a film, then the image is transferred from film to the card. This technique is suitable for edge-to-edge printing, heavy duty printing, improves reliability and thus suitable for a large variety of card types, such as:

- Travel ID cards
- Identity cards
- Student cards
- Entry permit cards
- High quality card applications
- Finance cards
- Resident cards
- Driving Licenses

## TECHNICAL DATA

<b>Print Method</b>	Colour dye sublimation retransfer technology
<b>Resolution</b>	600 dpi
<b>Print Capability</b>	Single Side, Double Side, Over-the-Edge, photo quality image colour
<b>Print Speed</b>	Single Side: 25 sec. Double Side: 55 sec.
<b>Interfaces</b>	USB (2.0), Ethernet (10/100)
<b>Card Thickness</b>	0,5 - 1,25 mm (20 - 50 mil)
<b>Security Features</b>	RFID ribbon, card feeder lock, custom watermarks (BMP)
<b>Card Loading</b>	Auto card feeder for 250 cards (0,76 mm thickness) Manual feed: single card
<b>Card Types</b>	PVC, ABS, PET, PET-G, PC 85,6 x 53,98 mm (ISO ID-1/CR-80 size)
<b>Consumables</b>	Ribbon YMCK (500 Images), Ribbon YMCKH (400 Images), Ribbon YMCKK (400 Images), Ribbon YMCKI (400 Images), Ribbon YMCKSI (350 Images), Transfer Film YMCK (500 Images), Ribbon K (500 Images), Transfer Film K (500 Images), Ribbon YMCK for PatchIM (500 Images), PatchIM PP (250 Images)
<b>Cleaning Set</b>	Cleaning Card Cleaning Roller
<b>Physical Weight</b>	22 kg
<b>Physical Size</b>	339 x 311 x 431 mm (W x D x H)
<b>Noise</b>	55 dB(A) while printing 40 dB(A) in standby
<b>Power Voltage</b>	Auto wide ranging, 100 - 240 V AC - 50/60 Hz
<b>Environment</b>	Printing: +15° to +30° C Temperature; 35 - 95% Humidity Storage: +5° C to +45° C Temperature; 35 - 95% Humidity
<b>Driver</b>	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
<b>Optional Encoder</b>	Encoder prepared
<b>Warranty</b>	For more details please contact your local dealer



### DASCOM GB Ltd

Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

### DASCOM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

### DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047